

## Clamps & Couplings

### QUICK-FIX™ TELESCOPING REPAIR COUPLING

- Schedule 40
- 150 PSI Rated In All Positions
- Complies w/ASTM & ANSI
- One Piece Cylinder
- Internal High Quality Self-Lubricating EPDM O-ring



Part#	slip x spigot
234650	1/2"
234651	3/4"
234652	1" x 1"
234653	1-1/4"
234655	1-1/2"
234656	2"

### SNAP-FIX™ REPAIR COUPLING

- For C.P.V.C.
- Positive Snapping Lock Assures Strong Seal
- Permanent Seal



Part#	size
234660	1/2" C.P.V.C.
234665	3/4" C.P.V.C.

### PIPE REPAIR CLAMP - 3" LENGTH

- 301 Stainless Steel Shield
- Galvanized Malleable Iron Lugs
- Plated Long Neck Carriage Bolt & Nut
- High Content Neoprene Gasket



Part#	size
234670	1/2"
234671	3/4"
234672	1"
234673	1-1/4"
234675	1-1/2"
234677	2"

### P.V.C. COMPRESSION COUPLING

- Schedule 40



Part#	size
235310	1/2" IPS
235311	3/4" IPS
235312	1" IPS
235313	1-1/4" IPS
235314	1-1/2" IPS
235315	2" IPS
235316	3" IPS
235317	4" IPS

### C.P.V.C. COMPRESSION COUPLING

- C.P.V.C.



Part#	size
234680	1/2" IPS (5/8" O.D.)
234685	3/4" IPS (7/8" O.D.)

## Clamps & Couplings

### STAINLESS STEEL CLAMP

- 1/2" Wide Band
- Slotted 5/16" Hex Head
- Zinc Plated Carbon Steel Screw



Part#	size
234690	#4 7/32" to 5/8" (1/4" band)
234691	#6 7/16" to 25/32"
234693	#8 1/2" to 29/32"
234695	#10 9/16" to 1-1/16"
234697	#12 11/16" to 1-1/4"
234698	#16 13/16" to 1-1/2"
234699	#20 13/16" to 1-3/4"
234700	#24 1-1/16" to 2"
234701	#28 1-5/16" to 2-1/4"
234702	#32 1-9/16" to 2-1/2"
234703	#36 1-13/16" to 2-3/4"
234704	#40 2-1/16" to 3"
234705	#52 2-13/16" to 3-3/4"
234706	#72 4-1/8" to 5"
234707	#88 5-1/8" to 6"

### STAINLESS STEEL HOSE CLAMP

- 1/2" Wide Band
- Slotted 5/16" Hex Head
- Stainless Steel Screw



Part#	size
234710	#4 7/32" to 5/8" (1/4" band)
234711	#6 7/16" to 25/32"
234713	#8 1/2" to 29/32"
234715	#10 9/16" to 1-1/16"
234717	#12 11/16" to 1-1/4"
234718	#16 13/16" to 1-1/2"
234719	#20 13/16" to 1-3/4"
234720	#24 1-1/16" to 2"
234721	#28 1-5/16" to 2-1/4"
234723	#32 1-9/16" to 2-1/2"
234725	#40 2-1/16" to 3"
234727	#72 4-1/8" to 5"
234729	#88 5-1/8" to 6"