

## Plumbing Supplies

### ZOOM SPOUT OILER

- High Grade Turbine Oil
- Spout Adjusts To 14" Length



**Part#**  
221000

**size**  
4 oz. squeeze  
bottle

### ZOOM SPOUT RUST REMOVER

- Fast Acting Super Penetrate
- Spout Adjusts To 14" Length



**Part#**  
221100

**size**  
4 oz. plastic  
bottle

## Solder

### 50/50 WIRE SOLDER

- Made Of Tin & Lead
- Meets ASTM B-32 Specs.
- 415°F Melting Temperature
- 6950 PSI Tensile Strength
- For Heating Systems/Non Potable Water



**Part#**  
221120

**size**  
1 lb.

### 97/3 WIRE SOLDER

- Economy Tin, Copper Alloy Wide Paste Range
- 445°F Melting Temperature
- 5800 PSI Tensile Strength



**Part#**  
221125  
221127

**size**  
1/2 lb.  
1 lb.

### LEAD FREE WIRE SOLDER

- Economy Tin, Copper, Silver Alloy Wide Paste Range
- 440°F Melting Temperature
- 6800 PSI Tensile Strength



**Part#**  
221130  
221135

**size**  
1/2 lb.  
1 lb.

## Solder

### LEAD FREE WIRE SOLDER

- Meets ASTM B-32 Alloy TC Specs
- 410°F Melting Temperature
- 7130 PSI Tensile Strength



**Part#**  
221140  
221145

**size**  
1/2 lb.  
1 lb.

### SOLDER

#### 1 LB.

- Meets ASTM B-32 Alloy TC Specs
- 361°F Melting Temperature
- 7130 PSI Tensile Strength



**Part#**  
221150  
221155  
221157

**size**  
50/50 wire  
50/50 acid wire  
97 tin/3 copper - lead free

## Solder Accessories

### BRAZING RODS

- 28 Rods Per Tube



**Part#**  
221170  
221175  
221177

**size**  
0% silver  
5% silver  
15% silver

### SOLDER FLUX

- Water Washable Paste Flux
- Meets ASTM B-813 Standards
- Use With 95/5, 60/40, 50/50 & 40/60



**Part#**  
221180  
221185

**size**  
4 oz.  
16 oz.

### PETROLEUM TINNING FLUX

- Water Soluble
- Contains Zinc, Ammonia Chloride & Tin Powder
- For Pre-tinning Copper



**Part#**  
221190

**size**  
1.7 oz.